



Principal Dimension					Basic Load Rating		Fatigue	Speed Rating		Mass	Designation
d	D	T	B	C	Dynamic	Static	Load Limit	Reference Speed	Limiting Speed	kg	
mm					C	Co	Pu	Grease	Oil		
					kN		kN	RPM			
65	100	23	23	17,5	96,5	127	14	5000	6000	0,63	32013X
	100	27	27	21	110	153	17,3	5000	6300	0,78	33013
	110	28	28	22,5	143	283	21,2	4800	6300	1,05	JM 511946/910
	110	31	31	25	138	193	22,4	4300	6300	1,15	T2DD 065
	110	34	34	26,5	142	208	24	4300	5600	1,30	33113
	120	24,75	23	20	132	134	16,3	4500	5600	1,15	30213
	120	32,75	31	27	151	193	22,8	4000	5600	1,50	32213
	120	41	41	32	194	270	30,5	3800	5300	2,05	33213
	130	37	33,5	26	180	216	25,5	3800	5000	2,20	T7FC 065
	140	36	33	28	194	228	27,5	3600	4800	2,40	30313
	140	36	33	23	190	193	23,6	3600	4800	2,35	31313
140	51	48	39	264	335	40	3400	4800	3,45	32313	
70	110	25	25	19	116	153	17,3	4500	5600	0,84	32014 X
	110	31	31	25,5	130	196	22,8	4300	5600	1,10	33014
	120	37	37	29	172	250	30	4000	5300	1,70	33114
	125	26,25	24	21	125	156	18	4000	5300	1,25	30214
	125	33,25	31	27	157	208	24,5	3800	5300	1,60	32214
	125	41	41	32	201	285	32,5	3600	5000	2,10	33214
	130	43	42	35	233	325	38	3800	5600	2,45	T2ED 070
	140	39	35,5	27	204	240	27,5	3400	4500	2,65	T7FC 070
	150	38	35	30	220	260	34	3400	4500	2,90	30314
	150	38	35	25	216	220	27	3400	4500	2,95	31314
	150	54	51	42	297	380	45	3200	4500	4,30	32314
75	105	20	20	16	81,5	116	13,2	4800	6300	0,52	32915
	115	25	25	19	122	163	18,6	4300	5300	0,90	32015
	115	31	31	25,5	134	228	26	4000	5300	1,15	33015
	120	31	29,5	25	160	216	25	4300	5600	1,30	JM714249/210
	125	37	37	29	176	265	31,5	3800	5000	1,80	33115
	130	27,25	25	22	140	176	20,4	3800	5000	1,40	30215
	130	33,25	31	27	161	212	24,5	3600	5000	1,70	32215
	130	41	41	31	209	300	34	3400	4800	2,25	33215
	150	42	38	29	232	280	31	3200	4300	3,25	T7FC 075
	160	40	37	31	246	290	34	3200	4300	3,45	30315
	160	40	37	26	240	245	29	3200	4300	3,50	31315
160	58	55	45	336	440	51	3000	4300	5,20	32315	
80	125	29	29	22	138	216	24,5	3600	5000	1,30	32016X
	125	36	36	29,5	168	285	32	3600	5000	1,65	33016
	130	35	38	31,5	176	275	32,5	3600	5300	1,70	JM 515649/610
	130	37	37	29	179	280	32,5	3600	4800	1,90	33116
	140	28,25	26	22	151	183	21,2	3400	4800	1,60	30216
	140	35,25	33	28	187	245	28,5	3400	4500	2,05	32216
	140	46	46	35	251	375	41,5	3200	4500	2,90	33216
	160	45	41	31	260	315	35,5	3000	4000	3,95	T7FC 080
	170	42,5	39	33	270	320	38	3000	4300	4,10	30316
	170	42,5	39	27	260	265	32	3000	4000	4,05	31316
	170	61,5	58	48	380	500	57	3000	4300	6,20	32316