



d mm	Boundary Dimensions				Basic Load Rating		Limiting Speeds		WT kg	Bearing Number
	D	T	B	C	Dynamic	Static	Grease	Oil		
					C	C ₀	RPM	RPM		
95.250	130.175	20.638	21.433	16.670	81.0	147	2500	3300	0.789	L319249/L319210
	146.050	33.338	34.925	26.195	163	266	2400	3100	1.95	47896/47820
	147.638	35.717	36.322	26.192	180	279	2300	3100	2.09	594A/592*E
	148.430	28.575	28.971	21.433	138	215	2300	3100	1.75	42375/42584
	152.400	39.688	36.322	30.162	180	279	2300	3100	2.51	594/592A
	157.162	36.512	36.116	26.195	188	305	2200	2900	2.76	52375/52618
	168.275	41.275	41.275	30.162	222	340	2100	2800	3.72	683/672
190.500	57.150	57.531	46.038	445	610	1900	2600	7.5	HH221440/HH221410	
96.838	148.430	28.575	28.971	21.433	138	215	2300	3100	1.69	42381/42584
	188.912	50.800	46.038	31.750	281	365	1800	2400	5.67	90381/90744
98.425	157.162	36.512	36.116	26.195	188	305	2200	2900	2.62	52387/52618
	168.275	41.275	41.275	30.162	222	340	2100	2800	3.56	685/672
99.974	212.725	66.675	66.675	53.975	575	810	1700	2300	11.5	HH224334/HH224310
100.000	155.000	36.000	35.000	28.000	192	310	2200	2900	2.4	JM720249/JM720210
100.012	157.162	36.512	36.116	26.195	188	305	2200	2900	2.55	52393/52618
101.600	157.162	36.512	36.116	26.195	188	305	2200	2900	2.48	52400/52618
	168.275	41.275	41.275	30.162	222	340	2100	2800	3.4	687/672
	180.975	47.625	48.006	38.100	285	430	2000	2700	5.11	780/772
	190.500	57.150	57.531	44.450	380	555	2000	2600	7	861/854
	190.500	57.150	57.531	46.038	445	610	1900	2600	7.06	HH221449/HH221410
	190.500	57.150	57.531	46.038	445	610	1900	2600	7.06	HH221449A/HH221410
	212.725	66.675	66.675	53.975	475	695	1800	2300	11.2	941/932
	212.725	66.675	66.675	53.975	575	810	1700	2300	11.3	HH224335/HH224310
158.750	23.020	21.438	15.875	102	166	2100	2800	1.37	37425/37625	
107.950	159.987	34.925	34.925	26.988	167	320	2100	2800	2.37	LM522546/LM522510
	165.100	36.512	36.512	26.988	191	315	2100	2700	2.69	56425/56650
	212.725	66.675	66.675	53.975	475	695	1800	2300	10.7	936/932
109.538	158.750	23.020	21.438	15.875	102	166	2100	2800	1.33	37431/37625
109.987	159.987	34.925	34.925	26.988	167	320	2100	2800	2.24	LM522548/LM522510
109.992	177.800	41.275	41.275	30.162	232	375	1900	2600	3.77	64433/64700
110.000	165.000	35.000	35.000	26.500	191	315	2100	2700	2.52	JM822049/JM822010
	180.000	47.000	46.000	38.000	305	480	1900	2600	4.61	JHM522649/JHM522610
111.125	214.312	55.562	52.388	39.688	405	560	1500	2000	8.18	H924045/H924010
114.300	177.800	41.275	41.275	30.162	232	375	1900	2600	3.52	64450/64700
	180.975	34.925	31.750	25.400	169	245	1900	2500	2.93	68450/68712
	212.725	66.675	66.675	53.975	475	695	1800	2300	10.1	938/932
	212.725	66.675	66.675	53.975	575	810	1700	2300	10.2	HH224346/HH224310
	228.600	53.975	49.428	38.100	430	620	1400	1900	9.76	HM926740/HM926710

